

#### **DATA SHEET**

# **SKY66397-12: 2300 to 2700 MHz Wide Instantaneous Bandwidth High-Efficiency Power Amplifier**

## **Applications**

- FDD and TDD 2G/3G/4G LTE systems
- 3GPP bands 7, 38, and 41 small-cell base stations
- · Driver amplifier for micro-base and macro-base stations
- · Active antenna array and massive MIMO

#### **Features**

- High-efficiency: PAE = 35% @ +28 dBm
- High linearity: +28 dBm with < -50 dBc ACLR with pre-distortion (40 MHz LTE, 8.5 dB PAR signal)
- High gain: 35 dB
- Excellent input and output return loss: to 50  $\Omega$  system
- Integrated active bias: performance compensated over temp
- Integrated enable On/Off function: PAEN = 1.5 to 2.5 V
- Single supply voltage: 5.0 V
- Pin-to-pin compatible PA family supporting all 3GPP bands
- Compact (16-pin, 5 × 5 × 1.3 mm) package (MSL3, 260 °C per JEDEC J-STD-020)

## **Description**

The SKY66397-12 is a high-efficiency fully input/output matched power amplifier (PA) with high gain and linearity. The compact  $5 \times 5$  mm PA is designed for FDD and TDD 2G/3G/4G LTE small cell base stations operating from 2300 to 2700 MHz. The active biasing circuitry is integrated to compensate PA performance over temperature, voltage, and process variation.

The SKY66397-12 is part of high-efficiency, pin-to-pin compatible PA family supporting all 3GPP bands. Table 1 lists the pin-to-pin compatible parts in the PA family.

A block diagram of the SKY66397-12 is shown in Figure 1. The device package and pinout for the device are shown in Figure 2. Signal pin assignments and functional pin descriptions are described in Table 2.

**Table 1. Pin-to-Pin Compatible PA Family** 

Part Number	Frequency (MHz)	3GPP Band
SKY66391-12	1800 to 1900	Bands 3 and 9
SKY66399-11	1900 to 2000	Bands 2, 25, 33, 36, and 37
SKY66394-11	2000 to 2300	Bands 1, 4, 10, and 23
SKY66397-12	2300 to 2700	Bands 7, 38, and 41





Skyworks Green™ products are compliant with all applicable legislation and are halogen-free. For additional information, refer to Skyworks Definition of Green<sup>™</sup>, document number SQ04-0074.




Figure 1. SKY66397-12 Block Diagram




Figure 2. SKY66397-12 Pinout (Top View)

Table 2. SKY66397-12 Signal Descriptions<sup>1</sup>

IUDIO EI O	and all oktobbot 12 digital bootspaces					
Pin	Name	Description	Pin	Name	Description	
1	GND	Ground	9	RFOUT	RF output port	
2	RFIN	RF input port	10	GND	Ground	
3	GND	Ground	11	GND	Ground	
4	GND	Ground	12	VCC3	Stage 3 collector voltage	
5	VBIAS	Bias voltage	13	GND	Ground	
6	PAEN	PA enable	14	VCC2	Stage 2 collector voltage	
7	GND	Ground	15	GND	Ground	
8	GND	Ground	16	VCC1	Stage 1 collector voltage	

<sup>1</sup> The center ground pad must have a low inductance and low thermal resistance connection to the application's printed circuit board ground plane.

## **Technical Description**

The matching circuits are contained within the device. An on-chip active bias circuit is included within the device for both input and output stages, which provides excellent gain tracking over temperature and voltage variations.

The SKY66397-12 is internally matched for maximum output power and efficiency. The input and output stages are independently supplied using the VCC1, VCC2, and VCC3 supply lines (pins 16, 14, and 12, respectively). The DC control voltage that sets the bias is supplied by the VCBIAS signal (pin 5).

## **Electrical and Mechanical Specifications**

The absolute maximum ratings of the SKY66397-12 are provided in Table 3. Recommended operating conditions are specified in Table 4, and electrical specifications are provided in Table 5.

Typical performance characteristics are shown in Figures 3 through 16.

Table 3. SKY66397-12 Absolute Maximum Ratings<sup>1</sup>

Parameter	Symbol	Minimum	Maximum	Units
RF input power (CW)	Pin		+10	dBm
Supply voltage (VCC1, VCC2, VCC3, VBIAS)	Vcc		5.5	V
PA enable	VEN		3	V
Operating temperature	Tc	-40	+100	°C
Storage temperature	Тѕт	-55	+125	°C
Junction temperature	TJ		+150	°C
Power dissipation	PD		1.55	W
Device thermal resistance	θυς		20.5	°C/W
Electrostatic discharge:	ESD			
Charged Device Model (CDM) Human Body Model (HBM)			500 1000	V V

Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

**ESD HANDLING**: Although this device is designed to be as robust as possible, electrostatic discharge (ESD) can damage this device.

This device must be protected at all times from ESD when handling or transporting. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection.

Industry-standard ESD handling precautions should be used at all times.

**Table 4. SKY66397-12 Recommended Operating Conditions** 

Parameter	Symbol	Min	Тур	Max	Units
Supply voltage (VCC1, VCC2, VCC3, VBIAS)	VCC1, VCC2, VCC3, VBIAS	4.75	5	5.25	V
PA enable:	PAEN				
ON OFF		1.5	2.0 0	2.5 0.5	V V
PA enable current	IENABLE		1	12	μА
Operating frequency	f	2490		2690	MHz
Operating temperature	Tc	-40	+25	+85	°C

Table 5. SKY66397-12 Electrical Specifications<sup>1</sup> (Vcc1 = Vcc2 = Vcc3 = VBIAS = 5 V, PAEN = 2.0 V, f = 2630 MHz, Tc = +25 °C, Input/Output Load = 50  $\Omega$ , Unless Otherwise Noted)


Parameter	Symbol	Test Condition	Min	Тур	Max	Units
Frequency	f		2490		2690	MHz
Small signal gain	IS21I	PIN = -30 dBm	34.5	36		dB
Gain @ +28 dBm	S21 @+28dBm	Pout = +28 dBm	36	37		dB
Input return loss	IS11I	PIN = -20 dBm	11	12		dB
Output return loss	IS22I	PIN = -20 dBm	8	10		dB
Reverse isolation <sup>2</sup>	IS12l	PIN = -30 dBm		50		dB
ACLR @ +28 dBm	ACLR	Pout = +28 dBm (2x20 MHz LTE, 8.5 dB PAR signal)		-33	-28	dBc
Output power at 3dB gain compression	P3dB	CW, reference to small signal gain (PIN= -30 dBm)	+34.5	+35.5		dBm
2 <sup>nd</sup> harmonic	2f0	CW, Pout = +28 dBm		-45	-38	dBc
3 <sup>rd</sup> harmonic <sup>2</sup>	3fo	CW, Pout = +28 dBm		-36		dBc
Power-added efficiency	PAE	CW, Pout = +28 dBm	30	33		%
Quiescent current	Iccq	No RF signal		95	125	mA
Turn-on time	ton	Measured from 50% PA enable voltage level to 90% of RF amplitude		1.2		us

Performance is guaranteed only under the conditions listed in this table.

Not tested in production. Verified by design.

## **Typical Performance Characteristics**

(Vcc1 = Vcc2 = Vcc3 = VBIAS = 5 V, PAEN = 2.0 V, f = 2630 MHz, Tc = +25 °C, Input/Output Load = 50  $\Omega$ , Unless Otherwise Noted)



**Figure 3. PAE vs. POUT Across Frequency** 




Figure 4. PAE vs. POUT Across Temperature




Figure 5. LTE 2x20 MHz ACLR1 vs. POUT Across Frequency




Figure 6. LTE 2x20 MHz ACLR1 vs. POUT Across Temperature




Figure 7. Gain vs POUT Across Frequency





Figure 8. Gain vs POUT Across Temperature



**Figure 9. lop vs POUT Across Frequency** 




Figure 10. lop vs POUT Across Temperature




Figure 11. 2nd Harmonic @ +28 dBm (CW) vs Frequency Across Temperature




Figure 12. 3rd Harmonic @ +28 dBm (GW) vs Frequency Across Temperature




Figure 13. Small Signal Gain vs Frequency Across Temperature




Figure 14. Wide-Band S21 vs Frequency




Figure 15. S11 vs Frequency Across Temperature (PiN = -20 dBm)




Figure 16. S22 vs Frequency Across Temperature (PIN = -20 dBm)

## **Evaluation Board Description**

The SKY66397-12 Evaluation Board is used to test the performance of the SKY66397-12 PA. An application schematic is provided in Figure 17. Table 6 provides the Bill of Materials (BOM) list for Evaluation Board components.

An assembly drawing for the Evaluation Board is shown in Figure 18. Board layer details are shown in Figure 19. Layer detail physical characteristics are noted in Figure 20.

### **Circuit Design Considerations**

The following design considerations are general in nature and must be followed regardless of final use or configuration:

- Paths to ground should be made as short as possible.
- The ground pad of the SKY66397-12 has special electrical and thermal grounding requirements. This pad is the main thermal conduit for heat dissipation. Because the circuit board acts as the heat sink, it must shunt as much heat as possible from the device.

Therefore, design the connection to the ground pad to dissipate the maximum wattage produced by the circuit board. Multiple vias to the grounding layer are required.

**NOTE:** A poor connection between the ground pad and ground increases junction temperature (T<sub>J</sub>), which reduces the life of the device.

#### **Evaluation Board Test Procedure**

#### Turn-On Sequence

- 1. Connect 50  $\Omega$  Test Equipment or Load to the input and output RF ports of the Evaluation Board.
- 2. Connect the DC ground.
- 3. Connect all VCCs and VBIAS lines to a +5 V supply. Connect PAEN to a 2.0 V supply.
- 4. Without applying RF, turn on the 5 V supply, then turn on the 2 V PAFN.
- 5. Apply RF signal data at -30 dBm and observe that the gain of the device is approximately 36 dB. Begin measurements.

#### Turn-Off Sequence

- 1. Turn off the RF input to the device.
- 2. Turn off PAEN (set to 0 V).
- 3. Turn off all VCCs and VBIAS.

**NOTE:** It is important to adjust the VCC voltage sources so that +5 V is measured at the board. High collector currents drop the collector voltage significantly if long leads are used. Adjust the bias voltage to compensate.





Figure 17. SKY66397-12 Application Schematic


Table. 6. SKY66397-12 Evaluation Board Bill of Materials (BOM)


Component	Description	Size
C1	Resistor, 0 Ω, 0.063 W	0402
C3	Ceramic capacitor, 1 µF, ±10%, 16 V	0402
C4, C7	Ceramic capacitor, 3300 pF, X7R, ±10%, 50 V	0402
C6, C9, C11	Ceramic capacitor, 0.47 μF	0402
C8, C10, C12	Capacitor, optional 10 μF, X7R, ±10%, 16 V	1206
L1	DNI	




- 1. Evaluation Board Gerber files are available on request.
- 2. The C1 component shown in this assembly is a  $0 \Omega$  resistor.
- 3. The L1 component shown in this assembly is DNI.

**Figure 18. Evaluation Board Assembly Drawing** 






Layer 2







Layer 4

Figure 19. Board Layer Detail

50 Ohm	Cross Section	Name	Thickness (mm)	Materials
W = 0.500 mm		TMask L1 Dielectric L2 Dielectric L3 Dielectric L4 BMask	0.035 0.350 0.035	Solder Resist Cu, 1 oz. R04350 Cu, 1 oz. FR4 Cu, 1 oz. FR4 Cu, 1 oz. Solder Resist

204669-020

Figure 20. Layer Detail Physical Characteristics

## **Application Circuit Notes**

**Center Ground**. It is extremely important to sufficiently ground the bottom ground pad of the device for both thermal and stability reasons. Multiple small vias are acceptable and work well under the device if solder migration is an issue.

**GND** (pins 1, 3, 4, 7, 8, 10, 11, 13, and 15). Attach all ground pins to the RF ground plane with the largest diameter and lowest inductance via that the layout allows. Multiple small vias are acceptable and will work well under the device if solder migration is an issue.

**VCBIAS** (pin 5). The bias supply voltage for each stage, nominally set to +5 V.

**RFOUT** (**pin 9**). Amplifier RF output pin ( $Z_0 = 50 \Omega$ ). The module includes an internal DC blocking capacitor. All impedance matching is provided internal to the module.

**VCC1**, **VCC2**, and **VCC3** (pins 16, 14, and 12, respectively). Supply voltage for each stage collector bias is nominally set to 5 V. The evaluation board has inductors L1 and L2. These are place holders, and should be populated with 0  $\Omega$  resistors. Bypass and decoupling capacitors C6 through C12 should be placed in the approximate location shown on the evaluation board assembly drawing, although exact placement is not critical.

**RFIN** (pin 2). Amplifier RF input pin (Zo = 50  $\Omega$ ). All impedance matching is provided internal to the module.

## **Package Dimensions**

Typical part marking for the device is shown in Figure 21. The PCB layout footprint for the SKY66397-12 is shown in Figure 22. Package dimensions are shown in Figure 23, and tape and reel dimensions are provided in Figure 24.

## **Package and Handling Information**

Since the device package is sensitive to moisture absorption, it is baked and vacuum packed before shipping. Instructions on the shipping container label regarding exposure to moisture after the container seal is broken must be followed. Otherwise, problems related to moisture absorption may occur when the part is subjected to high temperature during solder assembly.

The SKY66397-12 is rated to Moisture Sensitivity Level 3 (MSL3) at 260 °C. It can be used for lead or lead-free soldering. For additional information, refer to Skyworks Application Note, *PCB Design and SMT Assembly/Rework Guidelines for MCM-L Packages*, document number 101752.

Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment. Production quantities of this product are shipped in a standard tape and reel format.





Figure 21. SKY66397-12 Typical Part Marking




#### Notes:

- 1. Thermal vias should be resin filled and capped in accordance with IPC-4761 type VII vias.
- 2. Recommended Cu thickness is 30 to 35  $\mu m$

204669-022

Figure 22. SKY66397-12 PCB Layout Footprint




1. Dimensions are in millimeters (unless otherwise specified).

2. Dimensions and tolerances are in accordance with ASME Y14.5M-1994.

204669-023

Figure 23. SKY66397-23 Package Dimensions



2. Carrier tape shall be black conductive polycarbonate.

3. Cover tape shall be transparent conductive material.

- 4. ESD-surface resistivity shall be  $\leq 1 \times 10^{10} \Omega$ /square per EJA, JEDEC TNR specification.
- 5. All measurements are in millimeters.

204669-024

Figure 24. SKY66397-12 Tape and Reel Dimensions

## **Ordering Information**

Part Number	Product Description	<b>Evaluation Board Part Number</b>	
SKY66397-12	2300 to 2700 MHz Wide Instantaneous High-Efficiency PA	SKY66397-12EK1	

Copyright © 2017-2019 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks and the Skyworks symbol are trademarks or registered trademarks of Skyworks Solutions, Inc. or its subsidiaries in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com, are incorporated by reference.